

ITW SHAKEPROOF INDUSTRIAL PRODUCTS

FINISH
CODE

REVISION
LEVEL

BRIEF DESCRIPTION:

HVY ZINC PHOS-OIL

LQ

1

REV DATE: 07/27/2010

GENERAL DESCRIPTION

HEAVY ZINC PHOSPHATE AND OIL

APPEARANCE

GRAY TO BLACK APPEARANCE

ADHESION AND DUCTILITY

TO BE TESTED IN ACCORDANCE TO ASTM B571 (SCOTCH TAPE TEST)

CORROSION REQUIREMENTS

RED RUST: 100

WHITE CORRIOSION: 0

SALT SPRAY TESTS TO BE PERFORMED PER ASTM B117

COATING THICKNESS REQUIREMENTS

MIN THICKNESS: 2000MIL/FT2 MAX THICKNESS: 0
THICKNESS SHALL BE TESTED PER ASTM E376

STRESS RELIEF

NOT REQUIRED

QUALITY CONTROL

VISUALLY INSPECT FOR UNIFORMITY OF COLOR & SURFACE APPEARANCE, FREEDOM FROM TEARS, BARE SPOT, POWDERY FILM. SLOUGHING OFF OF FILM & BLISTERING, OR EXCESSIVE OIL

EQUIVALENT SPECS

GM 6035M

APPROVED SUPPLIERS:

PRINT DATE:
07/27/2010