

ITW SHAKEPROOF INDUSTRIAL PRODUCTS

FINISH
CODE

REVISION
LEVEL

BRIEF DESCRIPTION:

MZINC-CLR CHRMAT-RoHS

SB

1

REV DATE: 4/1/2007

GENERAL DESCRIPTION

MECHANICALLY DEPOSITED ZINC PLATING ON STEEL WITH A MINIMUM THICKNESS OF .00015" WITH A SINGLE DIP OF CLEAR CHROMATE !!!MUST BE RoHS COMPLIANT!!!

APPEARANCE

BRIGHT SILVERY TO SILVERY WITH BLUISH TINT APPEARANCE

ADHESION AND DUCTILITY

TO BE TESTED IN ACCORDANCE TO ASTM B571 (SCOTCH TAPE TEST)

CORROSION REQUIREMENTS

RED RUST: 24

WHITE CORROSION: 12

SALT SPRAY TESTS TO BE PERFORMED PER ASTM B117

COATING THICKNESS REQUIREMENTS

MIN THICKNESS: .00015 MAX THICKNESS: .00035
THICKNESS SHALL BE TESTED PER ASTM E376

STRESS RELIEF

NOT REQUIRED

QUALITY CONTROL

VISUALLY INSPECT FOR UNIFORMITY OF COLOR & SURFACE APPEARANCE, FREEDOM FROM TEARS, BARE SPOT, POWDERY FILM. SLOUGHING OFF OF FILM & BLISTERING

EQUIVALENT SPECS

ASTM B695

APPROVED SUPPLIERS:

PRINT DATE:
3/19/2007